IT6823 72V / 1.5A / 108W





IT6823 72V / 1.5A / 108W

Compact, affordable **programmable** Power supply
The IT6800-series of programmable dc power supplies give you the performance of
system power supplies without the high price. All models give you clean power,
dependable regulation and programmable with GPIB, USB and RS-232 interface. IT6800series are designed to meet the most demanding applications with high performance and
reliability you can count on

Feature

- Liner Programmable Power supply
- USB/GPIB/RS232 Interface
- Intellective fan cooling
- SCPI Compatible
- VFD Display

Specifications

- Low noise and ripple output
- CV / CC Mode
- ½2U Standard 19" rack or bench top install
- Convenient numeric keypad
- Over current and temperature protection

| - Specifications | | |
|---------------------|-------------|---|
| Output Ratings | Voltage | 0-72V |
| | Current | 0-1.5A |
| Load Regulation | Voltage | <0.01%+3mV |
| | Current | < 0.01% + 3mA |
| Line Regulation | Voltage | <0.01%+3mV |
| | Current | <0.1%+2mA |
| Setup Resolution | Voltage | 10mV |
| | Current | 10mA |
| Setup Accuracy | Voltage | $\leq 0.05\% + 15 \text{mV}$ |
| | Current | $\leq 0.2\% + 10$ mA |
| Readback Resolution | Voltage | $10 \text{mV} (<\!\!20 \text{V}) / 100 \text{mV} (\geq\!\!20 \text{V})$ |
| | Current | 10mA |
| Readback Accuracy | Voltage<20V | $\leq 0.05\% + 20 \text{mV}$ |
| | Voltage≥20V | $\leq 0.05\% + 120 \text{mV}$ |

Current <0.1%+15mARipple(20-20MHz) Voltage $\leq 0.5 \text{mVrms/}4 \text{mVp-p}$ Current ≤5mArms Temperature Operating 0 to 40 ≤ 75 R.H. -15 to 70 Storage ≤ 85 R.H. Dimension W*H*D(mm)214.5 * 88.2 * 354.6

Net

■ Standard Accessories

AC Line Cord

Weight

- USER Manual
- Calibration Report

Optional Accessories

7.7Kg

- IT-E131 RS232 Communication Cable
- IT-E132 USB Communication Cable
- IT-E133 GPIB Communication Cable
- IT-E151 19" Rack Mount Kit